



Quality Bathtub & Ceramic
Tile Refinishing Since 1985

Call Us for a Free Quote:
847-776-0050

IMMEDIATE INSTRUCTIONS

1. The remaining protective paper and masking tape should be carefully removed between 24 and 48 hours after refinishing.
2. **WATER MUST NOT BE USED ON REFINISHED SURFACES UNTIL THE FIFTH DAY FOLLOWING REFINISHING.**
3. **The bathtub hardware and caulking can be reinstalled on the fourth day after refinishing.**

CARE AND MAINTENANCE

Following the application, a chemical reaction with the original surface takes place. The two become fused during the next ninety days.

- Clean your newly refinished surfaces in the same manner as the originals. The bathtub should be cleaned and rinsed on a regular basis with products such as Lysol Tub & Tile Cleaner, Dow Scrubbing Bubbles, Scratch Guard or Mr. Clean Bathroom Cleaner. Harsh abrasive cleansers are unnecessary and can eventually ruin the finish. **DO NOT USE COMET OR KITCHEN CLEANSERS OR AN ABRASIVE SPONGE.** However, any chemicals you choose for cleaning **must** be tested in an inconspicuous area of the bathtub before general use. After the use of all chemicals thoroughly rinse with water.
- Do not allow anything to strike the surface.
- **Water should not be allowed to drip from faucets.** Such undo pressure can cause the finish to crack and wear prematurely.
- Bathmats can be used but **must be removed** immediately following use.

ADDITIONAL MAINTENANCE

- Iron and limestone in some water leave behind mineral stains which can be removed by the cautious use of mild acid solution, such as a toilet bowl cleaner. **Thoroughly rinse with water.**
- Dulling film from soap buildup may cause the surface to lose its glossy finish. Removal of film may be accomplished by the following method:
 - a. Clean and polish the dulled surface by rubbing briskly with a damp cloth heavily saturated with an automotive polish, and/or a heavy paste made from Bon Ami powder.
 - b. Rinse thoroughly with water, repeat step (a) if necessary.

OPTIONAL NON-SKID SURFACE

- The Non-Skid integral safety surface is a slip-resistant aid while showering. Keep in mind that water and soap on any surface will contribute to and will increase the possibility of slipping. Therefore bathe with care.
- The Non-Skid can be cleaned with a laundry detergent, either liquid or granular. An abrasive can be used **only** on the Non-Skid surface.